

Bs215

The **Bs215** by SHERMANN Audio is a compact, high power LF drive system supplied in touring or install finish.

Two British built, efficient 15" LF drivers operate in a shared ported enclosure to provide smooth but extended response.

The cabinet may be used in vertical or horizontal format and also available with 4 x 100mm rear mounted swivel castors c/w with two additional handles for touring purposes.

Whilst the Bs215 reproduces low frequencies with ease it also has a solid, defined response over its entire operating range, a feature not always present in 15" loaded cabinets. This advantage allows more widespread use for the Bs215 in Clubs, Dance Venues, Theatres, Concert & Cabaret stages, larger Places of Worship and for use by rental companies.



The **Bs215** is equipped with two rugged, high power 15" bass drivers whose response is optimised for effective reproduction of low frequencies.

A rigid cone of optimal weight is driven by a 4" edge wound voice coil stabilised by a sturdy dual suspension system.

A massive magnet assembly enhanced by innovative cooling techniques is firmly secured to a robust cast aluminium chassis.

All SHERMANN Audio products are built to the highest standards and the Bs215 is no exception.

Constructed externally from 18mm birch plywood the loudspeaker baffle thickness is 25mm for ultimate rigidity and performance.

Connections

Speakon NL4 pin 1+ **hot** / pin 1- **cold**
Speakon NL8 pin 1+ **hot** / pin 1- **cold**

Crossover frequencies

External: high pass; -3dB @ 30Hz / 4th order
External: low pass; **110Hz** (within SHERMANN Audio systems)

Technical Specifications

System

Format	Reflex loading
Nom' impedance	4 or 8 ohm *
High pass filter	30Hz 4th order
Rec' amp' power @ 4ohm	750-1000 watts rms
Maximum peak power	1,200 watts
Recommended - x'over frequency	110 Hz

Performance

Sensitivity @ 1w/1m	100 dB
Maximum output	129 dB @ 1m
Frequency response	35 Hz - 150 Khz

Components

Drive units	381 mm (15") x 2
-------------	------------------

Dimensions

Height	883 mm (34.75")
Depth	608 mm (23.95")
Depth over castors (option)	736 mm (28.95")
Width	577 mm (22.70")
External volume	298 lts (10.5 ft ³)
Weight	62 Kgs (136 lbs)

Mechanical

Connectors	Speakon NL4 x 2
(option) *	Speakon NL8 x 2
Handles	Bar type (x 4)
Castors (option) *	4 x 100mm swivel
Pole mount / cabinet top (option) *	GSA1 (32, 35 or 38mm)
Finish	Black carpet

Please note

We would like to draw your attention to the likelihood of hearing damage from prolonged exposure to high sound pressure levels.

Care should be taken when using cabinets in close proximity to the audience, musicians or artists.

For further information on the safe operation of any SHERMANN Audio product please fax, call or email us - contact details are shown below.

* Options must be requested at time of ordering.



SHERMANN Audio

The Gx Series

Unit 35, Vastre Enterprise Park
 Newtown, Powys, UK.

SY16 1DZ

Tel: +44 (0)8456 44 22 09 (01686 622 997)

Fax: +44 (0)8456 44 22 51

Email: sales@shermann.com

Web: www.shermann-audio.com