

Dx Series by Shermann

Bx218



Compact, highly portable LF cabinet with 2 powerful 18" bass drivers.

Standard fittings include pole mount adapter and rear mounted swivel castors c/w additional handles.

Our sturdy TPC coating is the finish used on this model.

Use with SHERMANN Audio Dx cabinets to form a cost-effective, powerful, high quality PA or Disco rig.

Components

Wiring	2.5mm multi-strand copper
Castors (option)	4 x 100mm swivel type on back
LF drivers	Cast chassis 18" / 4" voice coil

Connections

Speakon NL4	pin 1+ hot / pin 1- cold
Speakon NL8	pin 1+ hot / pin 1- cold

Crossover/filter frequencies

External:	High pass: -3dB @ 30Hz / 8th order
External:	Low pass: 110 Hz (within SHERMANN Audio systems)

Specifications

System

Format	Ported enclosure
Nom' impedance	4 ohm
Power @ 4ohm	2,000 watts rms

Performance

Sensitivity @ 1w/1m	100 dB
Maximum output	130 dB @ 1m
Frequency response	30 Hz - 120Hz
Dispersion (>2.5khz)	N/A

Components

Drive unit (LF)	458 mm (18") x 2
-----------------	------------------

Dimensions

Height	1035 mm
Depth	608 mm
Width	577 mm
Depth over castors (option)	736 mm
External volume	350 lts
Weight	70.3 Kgs

Mechanical

Connectors	"Speakon" NL4 x 2
(Option)	"Speakon" NL8 x 2
Castors	4 x 100mm swivel
Handles	Steel bar type
Pole mount	35mm / 20mm screw
Finish	SW-Coat / S-Coat
Foam Front / Welded	
Grille	Standard fitting

Please note

We would like to draw your attention to the likelihood of hearing damage from prolonged exposure to high sound pressure levels.

Care should be taken when using cabinets in close proximity to the audience, musicians or artists.

For further information on the safe operation of any Shermann Audio product please fax, call or email us - contact details are shown below.

* Options must be requested at time of ordering.



Shermann

Unit 3, Grooms Building,
Newtown, Powys.
SY16 1DL

Tel: +44 (0)1686 622 368
Mob: 07971 882663
Email: info@shermann.com
Web: www.shermann.com