

# Gx Series by SHERMANN Audio

## CB215

The **CB215** by Shermann is a compact, high power VLF drive system designed primarily for touring although installation versions may be supplied.



This superb Shermann model incorporates E.V-C alignment which augments the already stunning performance of the twin 15" drive units.

Standard fittings include 6 handles and easily replaced plywood skid sets on the back, base and side.

A strategically placed load strapping point is fitted on the back as a safety measure so that stacked boxes may be secured.

Four 100mm swivel castors complete this cost-effective, very efficient package.

The **CB215** is equipped with two rugged, high power 15" bass drivers whose response is optimised for effective reproduction of low frequencies.

A rigid cone of optimal weight is driven by a 4" edge wound voice coil stabilised by a sturdy dual suspension system.

A massive magnet assembly enhanced by innovative cooling techniques is firmly secured to a robust cast aluminium chassis.

All SHERMANN Audio products are built to the highest standards and the CB215 is no exception.

Constructed externally from 25mm birch plywood the loudspeaker baffle thickness is 25mm for ultimate rigidity and performance.

### Connections

**Speakon NL8** pin 1+ **hot** / pin 1- **cold**  
**Speakon NL4** pin 1+ **hot** / pin 1- **cold**  
**EP or AP types** to customer requirements

### Crossover/filter frequencies

**External:** High pass: **-3dB @ 30Hz / 4th order**  
**External:** Low pass: **110Hz** (within SHERMANN Audio systems)

### Technical Specifications

#### System

Format	Expanded V-Cavity <sup>o</sup>
Nom' impedance	4 or 8 ohm *
High pass filter	30Hz 4th order
Rec' amp' power @ 4ohm	550 - 1200 watts
Maximum peak power	1500 watts
Recommended - x'over frequency	110 Hz

#### Performance

Sensitivity @ 1w/1m	101 dB
Maximum output	131 dB @ 1m
Frequency response	45 Hz - 125 Khz

#### Components

Drive units	381 mm (15") x 2
-------------	------------------

#### Dimensions

Height	502 mm (19.75")
Depth	608 mm (23.95")
Depth over castors	735 mm (28.95")
Width	1021 mm (40.20")
External volume	296 lts (10.5 ft <sup>3</sup> )
Weight	71 Kgs (157 lbs)

#### Mechanical

Connectors	"Speakon" NL8 x 2
(Connector option) *	NL4 or EP types
Handles (sides)	Bar type ( x 4 )
Handles (ends)	Flip type ( x 2 )
Castors	4 x 100mm swivel
Finish	Black carpet

#### Please note

We would like to draw your attention to the likelihood of hearing damage from prolonged exposure to high sound pressure levels.

Care should be taken when using cabinets in close proximity to the audience, musicians or artists.

For further information on the safe operation of any SHERMANN Audio product please fax, call or email us - contact details are shown below.

\* Options must be requested at time of ordering.



**ShermannAudio**

Unit 35, Vastre Enterprise Park  
Newtown, Powys, UK.  
SY16 1DZ

Tel: 0845 644 2209  
Fax: 01 686 623 233  
Email: sales@shermann.com  
Web: [www.shermann.com](http://www.shermann.com)