

# Dx Series by Shermann

## DX-400

Also available as a  
multo-role version  
**VX-400**



*Now fitted with a sturdy welded  
mesh grille and foam front as standard*

The **DX-400** is a compact, two-way cabinet with an efficient **12"** bass/mid driver and powerful **1"** HF compression driver.

Premium quality, easily transported PA loudspeaker for conference, Theatre, AV and Club system applications.

Stunningly efficient, full-range general PA unit which may also be used with SHERMANN Audio bass cabs.

## Components

Crossover boards	2.4mm glass fibre / copper tracks
Capacitors	250v polypropylene (2% tolerance)
Inductors	1 & 1.25mm wire / air cored (2.5% tolerance)
Wiring	2.5mm multi-strand copper
HF driver	1" ferro-fluid cooled driver on CD horn
LF driver	Steel framed 12" / 2.5" voice coil

### Connections

**Speakon NL4** pin 1+ **hot** / pin 1- **cold** (

### Crossover frequencies

**External:** 4th order 110 Hz (with SHERMANN Audio LF Systems)

### Specifications

#### System

Format	2 way Passive
Network	PCN-3
Nom' impedance	8ohm
Hi-pass filter (-3dB point)	35Hz / 4th order
Rec' amp' power @ 8ohm	175-450 watts rms
Programme power	700 watts

#### Performance

Sensitivity @ 1w/1m	99 dB
Maximum output	126 dB @ 1m
Frequency response	60 Hz - 18.5 KHz
Dispersion (>2.5khz)	70° x 40°

#### Components

Drive unit (LF/MF)	305 mm
Drive unit (HF)	25 mm
Horn unit	CD horn

#### Dimensions

Height	587 mm
Depth	361 mm
Width	380 mm
Apex height	415 mm
External volume	77 lts
Weight	22.5 Kgs

#### Mechanical

Connectors	"Speakon" NL4 x 2
Connecting pins	1+ 1-
Flying points (option)	GS-TA3
Handle - top	Steel Bar type
Handle - sides	Steel Flip type
Stand mount (fitted)	35mm


#### Please note

We would like to draw your attention to the likelihood of hearing damage from prolonged exposure to high sound pressure levels.

Care should be taken when using cabinets in close proximity to the audience, musicians or artists.

For further information on the safe operation of any SHERMANN Audio product please fax, call or email us - contact details are shown below.

\* Options must be requested at time of ordering.



**ShermannAudio**

Unit 35, Vastre Enterprise Park  
Newtown, Powys,  
SY16 1DZ

Tel: 0845 644 2209

Fax: 01 686 623 233

Email: sales@shermann.com

Web: [www.shermann.com](http://www.shermann.com)