

Dx Series by *ShermannAudio*

Mx650



Now supplied with Sherman engraved foam front and not a badged front as shown

The superb **Mx650** is a compact, low-profile stage wedge with an efficient **15"** bass/mid driver and a high quality **1.4"** HF driver mounted on a CD horn.

It serves as a premium quality, easily transported stage wedge for conference, worship bands, theatre, AV, club foldback systems and touring sound applications.

Mx650's may also be operated as a full-range, general purpose FOH PA unit when used with SHERMANN Audio bass cabs.

Available in pairs with left/right handed baffles.

Components

Crossover boards	2.4mm glass fibre / copper tracks
Capacitors	250v polypropylene (2% tolerance)
Inductors	1 & 1.25mm wire / air cored (2.5% tolerance)
Wiring	1.5 & 2.5mm multi-strand copper
HF driver	1.4" ferro-fluid cooled driver on CD horn
LF driver	Steel framed 15" / 3" voice coil

Connections

Speakon NL4 pin 1+ **hot** / pin 1- **cold**

Crossover frequencies

External: **4th order 110 Hz** (with SHERMANN Audio LF Systems)

Specifications

System

Format	2 way Passive
Network	PCN-3
Nom' impedance	8 ohm
Hi-pass filter (-3dB point)	35Hz / 4th order
Rec' amp' power @ 8ohm	250-600 watts rms
Programme power	1,000 watts peak

Performance

Sensitivity @ 1w/1m	99 dB
Maximum output	128 dB @ 1m
Frequency response	65 Hz - 18.5 KHz
Dispersion (>2.5kHz)	80° x 60°

Components

Drive unit (LF/MF)	380 mm (15")
Drive unit (HF)	25 mm (1.4")
Horn unit	CD horn

Dimensions

Height	443 mm
Depth	361 mm
Width	730 mm
Apex height	391 mm
External volume	102 lts
Weight	26.4 Kgs

Mechanical

Connectors	"Speakon" NL4 x 2
Connecting pins	1+ 1-
Flying brackets (option) *	(Please call)
Stand mount (option)*	GSA1/35
Handles	Steel Flip type
Foam front / Welded grille	Standard fitting

Please note

We would like to draw your attention to the likelihood of hearing damage from prolonged exposure to high sound pressure levels. Care should be taken when using cabinets in close proximity to the audience, musicians or artists. For further information on the safe operation of any Sherman Audio product please fax, call or email us - contact details are shown below. The front foam used on this cabinet is not fire retardant.

* Options must be requested at time of ordering.



ShermannAudio

Unit 35, Vastre Enterprise Park,
Newtown, Powys.
SY16 1DZ

Tel: +44 (0) 1686 622 997
Fax: +44 (0) 1686 623 233
Email: info@shermann.com
Web: www.shermann.com